

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE AND MANUFACTURER

1.1 Product Identifier: Custom-Color™ Match Tint Kit

Product Code: 1205-xx and 1202-xx

SDS# MTVCCTK

SDS Date September 26, 2018

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Product Use: Coloring of plugging epoxy in bowling balls in preparation for redrilling

Uses Advised Against: Avoid usage in enclosed spaces or with poor ventilation

1.3 Details of the Supplier of the Substance or Mixture

Manufacturer/Preparer: **Motiv Bowling**
18570 Trimble Court
Spring Lake, MI 49456

1.4 Emergency Telephone Number:

Emergency Response Information (ERI) telephone numbers are managed by PERS:

USA and Canada: 1-800-633-8253

International: 1-801-629-0667

Other Product Information: 1-800-235-8324

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS No.	EC Index No.	Weight %	Labels	EC Risk Phrases
Dipropyleneglycol diglycidyl ether	41638-13-5	Not Listed	>75%	None	R: 36/38, 43
Proprietary Pigments	Proprietary	Proprietary	<40%	None	R: 22, 36/37/38, 43

SECTION 3 - HAZARDS IDENTIFICATION

HMIS: Health: 1
Flammability: 1
Reactivity: 0

Key: 4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

NFPA: Health: 1
Flammability: 1
Reactivity: 0

Product EC Risk Phrases: R: 22, 36/37/38, 43
Product EC Safety Phrases: S: 15, 24/25, 27/28, 37/39
Product EC Labels Required: None

This product contains items which alone require the labeling and risk phrases shown above. The actual product labels and risk phrases may vary. They are warnings particular to the raw materials incorporated into this product. They are listed to inform the user that components in this product may cause these hazardous actions to occur in particular situations.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush immediately with water for 15 minutes or longer if irritation does not cease. Seek medical attention immediately.

SKIN: Clean affected area with soap and water until irritation ceases. Discard clothing contaminated by product. It is not recommended to remove resin from skin with solvents. Solvents only increase contact area, enhance skin penetration and dry out the skin.

INHALATION: Highly unlikely method of contamination unless heated or misted. Could be a respiratory irritant if sensitized. Remove from area and consult physician immediately. If breathing labored, administer oxygen.

INGESTION: Induce vomiting only if person is conscious. Product has a low order of acute oral toxicity.

SECTION 5 - FIRE-FIGHTING MEASURES

Flash Point: >200°F (79°C)

Extinguishing Media: Use water fog, foam, dry chemical or CO². Do not use a direct stream of water. Product will float and can reignite on the surface of the water.

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

Containers may rupture or melt when exposed to extreme heat.

No unusual fire or explosion hazards.

Material is considered a combustible liquid. Class IIIB

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Material may be soaked up with sand or other inert solids. Sweep up absorbed product and dispose of in accordance with local and federal regulations.

SECTION 7 - HANDLING AND STORAGE

Use protective gloves and avoid skin contact or breathing of fumes. Store at ambient temperatures. Do not allow to freeze or overheat. If overheating occurs, be sure to shake well prior to usage.

Do not store near or mix with strong acids, strong oxidizing agents and bases.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors.

PROTECTIVE CLOTHING: Avoid contact with eyes. Wear chemical goggles if splash or contact possible. Wear chemical resistant gloves and other clothing or vapor masks as required to minimize contact.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Various colored viscous oily liquid
Smell:	Oily epoxy smell
Vapor Density:	Not Applicable
Vapor Pressure:	< 1mm Hg
Solubility in H ₂ O:	Negligible
Specific Gravity:	>1.10

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will auto-polymerize at very high temperatures.

HAZARDOUS DECOMPOSITION: Fumes, carbon dioxide, carbon monoxide, acrid smoke, phenolics, and aldehydes.
CONDITIONS TO AVOID: High heat, amines, strong oxidizers, acids and bases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product has low acute oral toxicity. Chronic effects could include skin sensitization and lung irritation. No known carcinogenicity.

SECTION 12 - ECOLOGICAL INFORMATION

Not determined. Quantities involved in standard packaging suggest negligible impact probable.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of product by incineration in an approved chemical waste handling facility. Material once polymerized with hardener becomes relatively inert solid. Avoid landfilling of liquids. Since emptied container will contain residue from product, all labeled hazard precautions must be observed. If this material becomes a waste, it would not be a hazardous waste by RCRA criteria (40 CFR 261). Place in an appropriate disposal facility in compliance with local regulations.

SECTION 14 - SHIPPING INFORMATION

Bulk DOT & International Shipping Information:

UN Number: Not Regulated
Hazard Class: None
Label Required: None
UN Proper Shipping Name: Non Regulated Plastic Liquid

SECTION 15 - REGULATORY DATA

SARA Hazard Categories(311/312):

To the best of our knowledge, this product contains no chemical subjects in amounts requiring listing

Toxic Substances Control Act (TSCA) Inventory Status:

All of this product's components are listed by TSCA Inventory of Chemical Substances or are not required to be listed.

California Safe Drinking Water and Toxi Enforcement Act (Proposition 65)

None in quantities required

CA_65 C/A = the chemical identified with this code is known to the state of California to cause both cancer and birth defects or other reproductive harm.

SECTION 16 - OTHER INFORMATION

Explanation of Labeling Requirements, Safety Phrases and Risk Phrases

Xi - Irritant

S15: Keep away from heat
S24/25: Avoid contact with skin and eyes.
S27/28: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of soap and water.
S37/39: Wear suitable gloves and eye/face protection.
R22: Harmful if swallowed.
R36/37/38: Irritating to eyes, respiratory system and skin.

R43: May cause sensitization by skin contact.

Prepared by: W. Scott Wilbur
Update September 26, 2018: Switched ERI from ChemTrec to PERS

Disclaimers: The information provided in this document related to material content represents the Manufacturer's knowledge and belief, which may be based in whole or in part on information provided by suppliers to the Manufacturer. This is intended to answer commonly asked questions about products and is not intended to be a comprehensive listing of all substances that may be of interest or that may be regulated in this or other of the manufacturer's products, nor is it intended to be a comprehensive summary of any and all regulations that may apply to this product. Where substances are listed, their listing does not infer or constitute a judgment as to their safety, environmental or health impacts. Information is supplied upon the condition that the persons receiving the same will make their own determination as to its suitability for their purposes prior to use. Customers and Distributors are encouraged to consult with legal and regulatory experts to determine applicable regulations and personal protection methods in light of intended use of the product.

Limitation of Remedies and Liability: In the event any Product is proven not to conform with the information in this document, then to the extent permitted by law, the Manufacturer's entire liability and Buyer's exclusive remedy, will be at the Manufacturer's option either: (i) replacement of Product with a conforming product, or (ii) refund of the purchase price paid by the Buyer for each non-conforming Product, within a reasonable time after written notification with proof of said non-conformance and return of said Product to the Manufacturer. The Manufacturer shall not under any circumstances be liable for direct, incidental, special, or consequential damages (including but not limited to loss of profits, revenue, or business) related to or arising out of this certification, including, the use, misuse or inability to use the Product. Unless stated otherwise in writing, the foregoing language cannot be waived, modified, or supplemented in any manner whatsoever.